

Silon Tabond 3032 Adhesive Resin

Category : Polymer , Adhesive , Thermoplastic , Polyethylene (PE) , LDPE , LLDPE

Material Notes:

Tabond 3032 is a chemically modified LDPE / LLDPE. Its functional groups improve considerably the bonding between polar polymers, for film applications. Characteristics: â€¢ Strong adhesion to PA / PE â€¢ Adhesion durability â€¢ Polyolefin like properties and processing â€¢ Easy handling during extrusion Information provided by Silon

Order this product through the following link:

http://www.lookpolymers.com/polymer_Silon-Tabond-3032-Adhesive-Resin.php

Physical Properties	Metric	English	Comments
Density	0.912 g/cc	0.0329 lb/inÂ³	
Melt Flow	2.0 g/10 min @Load 2.16 kg, Temperature 190 Â°C	2.0 g/10 min @Load 4.76 lb, Temperature 374 Â°F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	43.2	43.2	15s
Tensile Strength, Yield	8.10 MPa	1170 psi	
Elongation at Break	343 %	343 %	

Thermal Properties	Metric	English	Comments
Melting Point	120.1 Â°C	248.2 Â°F	DSC

Descriptive Properties	Value	Comments
Color	White	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China