

Solvay ALKAMULS® A Surfactant

Category: Fluid, Other Engineering Material, Additive/Filler for Polymer

Material Notes:

Identification: ETHOXYLATED OLEIC ACIDCAS: 9004 â€" 96 â€" 0Available in: Asia Pacific, Europe, Latin America and North America Solubility: Dispersible in water. Soluble in most polar and aromatic solvents. Applications: Agrochemical formulation: Low HLB, emulsifier. Surfactant of choice for biodegradable and low toxicity EC formulation. Fabric and Home Care: Emulsifier. Metal treatment: Nonionic emulsifier for metal working formulations with a HLB of 9.7. Recommended for cutting fluids used in aluminum machining. Used in the formulation of water based lubricants, often combined with an anionic emulsifier like Geropon HW15 or Lubrhophos LB400.Information provided by Rhodia, Rhodia has been acquired by Solvay.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-ALKAMULS-A-Surfactant.php

Physical Properties	Metric	English	Comments
Density	1.00 g/cc	0.0361 lb/in³	
рН	6.0 - 8.0	6.0 - 8.0	5% in water; RPG02

Thermal Properties	Metric	English	Comments
Pour Point	<= 0.000 °C	<= 32.0 °F	
Flash Point	>= 100 °C	>= 212 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.50 %	<= 0.50 %	RPG16
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Appearance	Liquid	
Composition	Active content	1
Ionic Charge	Nonionic	
Saponification number	95-105 mg KOH/g	RPG05

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842



Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China