

Solvay Chemicals NOCOLOK® Flux P2 Potassium Fluoroaluminate

Category : Ceramic

Material Notes:

Mixtures of NOCOLOK® Flux P2 with NOCOLOK® Flux allow for gradual viscosity adjustments in suspensions to suit specific process conditions. HS No.: 38109090 / CAS-No.: 60304-36-1 Uses: Automotive Sector, Commercial & Residential Air Conditioning, Refrigeration and Household & Electrical Appliances Information provided by Solvay

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Chemicals-NOCOLOK-Flux-P2-Potassium-Fluoroaluminate.php

Physical Properties	Metric	English	Comments
Bulk Density	0.350 - 0.550 g/cc	0.0126 - 0.0199 lb/in ³	
Density	2.80 - 3.00 g/cc @Temperature 20.0 °C	0.101 - 0.108 lb/in ³ @Temperature 68.0 °F	
Solubility in Water	0.45 %	0.45 %	
Particle Size	2.0 - 6.0 µm	2.0 - 6.0 µm	X50%

Thermal Properties	Metric	English	Comments
Melting Point	565 - 572 °C	1050 - 1060 °F	

Descriptive Properties	Value	Comments
Appearance	White powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China