

Solvay Specialty Polymers Algoflon® L203F Polytetrafluoroethylene (PTFE)

Category: Polymer, Thermoplastic, Fluoropolymer, PTFE, PTFE Powder

Material Notes:

Algoflon® L203F a white PTFE micronized powder produced from dispersion polymerization comprising loose agglomerates of submicron sized primary particles. Algoflon® L203F can be de-agglomerated to sub-micron particle size by the application of shear providing a better dispersion and distribution of the PTFE particles in the application. Designed for use in critical engineering and high end performance lubricants to improve thickening effect, lubricity, Algoflon® L203F improves also corrosion and temperature resistance.Uses: AdditiveAdditional Properties: Average Particle Size - Internal Method 5.0 µm; Bulk Density - ASTM D3418 325 g/l; Specific Surface Area - Internal Method > 7.5 m²/glnformation provided by Solvay Specialty Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-Specialty-Polymers-Algoflon-L203F-Polytetrafluoroethylene-PTFE.php

Thermal Properties	Metric	English	Comments
Melting Point	325 - 335 °C	617 - 635 °F	ASTM D3418

Descriptive Properties	Value	Comments
Availability	Asia Pacific	
	Europe	
	North America	
Color	White	
Form	Powder	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China