

## Solvay Specialty Polymers Algoflon® L206 Polytetrafluoroethylene (PTFE)

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE , PTFE Powder

### Material Notes:

Algoflon® L206 a white PTFE micronized powder produced from dispersion polymerization comprising loose agglomerates of sub-micron sized primary particles. Algoflon® L206 can be de-agglomerated to sub-micron particle size by the application of shear providing a better dispersion and distribution of the PTFE particles in the application. Designed for use in critical engineering and high end performance elastomers to improve abrasion and tear resistance, Algoflon® L206 is used as well in high performance coatings to improved non-stick properties, mar and abrasion resistance. Uses: Additive Additional Properties: Average Particle Size - Internal Method 5.0 µm; Bulk Density - ASTM D4895 325 g/l; Grind in Oil - NPIRI 1.50; Specific Surface Area - Internal Method > 7.5 m<sup>2</sup>/g Information provided by Solvay Specialty Polymers.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Solvay-Specialty-Polymers-Algoflon-L206-Polytetrafluoroethylene-PTFE.php](http://www.lookpolymers.com/polymer_Solvay-Specialty-Polymers-Algoflon-L206-Polytetrafluoroethylene-PTFE.php)

Thermal Properties	Metric	English	Comments
Melting Point	325 - 335 °C	617 - 635 °F	ASTM D3418

Descriptive Properties	Value	Comments
Availability	Asia Pacific	
	Europe	
	North America	
Color	White	
Form	Powder	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China