

## Solvay Specialty Polymers Tecnoflon® T 636/L Fluoroelastomer

Category: Polymer, Thermoset, Fluoropolymer, TS, Thermoset Fluoroelastomer, Rubber or Thermoset Elastomer (TSE)

## **Material Notes:**

TECNOFLON® T 636/L is a low viscosity fluoroelastomer terpolymer designed to provide improved low temperature characteristics. Tecnoflon® T 636/L does not contain curatives: therefore the proper levels of Tecnoflon® FOR M1 and Tecnoflon® FOR M2 must be added to achieve the required properties. Tecnoflon® T 636/L is a lower viscosity version of Tecnoflon® T 636: please refer to Tecnoflon® T 636 Technical data sheet for data on chemical resistance: Tecnoflon® T 636/L exhibits the same excellent heat and chemical resistance expected from Tecnoflon® copolymers. Features: Good Chemical Resistance; Good Flow; Good Mold Release; High Heat Resistance; Low Compression Set; Low Viscosity; TerpolymerUses: Belts/Belt Repair; Blending; Diaphragms; Gaskets; Hose; Low Temperature Applications; Profiles; Seals; SheetAdditional Properties: Fluorine Content - 66 %Information provided by Solvay Specialty Polymers.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Solvay-Specialty-Polymers-Tecnoflon-T-636L-Fluoroelastomer.php

Physical Properties	Metric	English	Comments
Mooney Viscosity	22	22	ML 1+10; ASTM D1646
	@Temperature 121 °C	@Temperature 250 °F	

Descriptive Properties	Value	Comments
Availability	Europe; North America	
Color	Translucent	
Form	Slab	
Processing Technique	Calendering; Compounding	
	Compression Molding; Extrusion	
	Injection Molding; Resin Transfer Molding	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China