

Solvay TECHNYLSTARâ,,¢ SX 216 V60 PA6, 60% glass filled, Conditioned

Category: Polymer, Thermoplastic, Nylon, Nylon 6, Nylon 6, 60% Glass Fiber Filled

Material Notes:

Description: TECHNYL STAR TM Polyamide reinforced with 60% of glass fiber, for injection molding. Characterized by a high fluidity of the melt. Available in: Europe and North America Product Applications: TECHNYLSTAR TM SX 216 V60 is suitable for all applications where a high rigidity is required. Due to its outstanding flow properties, the material easily fills the mould and the surface aspect of the finished part is excellent. This product is available in natural. Information provided by Rhodia, Rhodia has been acquired by Solvay.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Solvay-TECHNYLSTAR-SX-216-V60-PA6-60-glass-filled-Conditioned.php

Physical Properties	Metric	English	Comments
Density	1.65 g/cc	0.0596 lb/in³	ISO 1183/A

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	165 MPa	23900 psi	ISO 527 Type 1A
Elongation at Break	3.7 %	3.7 %	ISO 527 Type 1A
Tensile Modulus	15.5 GPa	2250 ksi	ISO 527 Type 1A
Flexural Modulus	13.2 GPa	1910 ksi	ISO 178
Izod Impact, Notched (ISO)	22.0 kJ/m²	10.5 ft-lb/in²	ISO 180/1eA
Izod Impact, Unnotched (ISO)	100 kJ/m²	47.6 ft-lb/in²	ISO 180/1eU
Charpy Impact Unnotched	9.50 J/cm²	45.2 ft-lb/in²	ISO 179/1eU
Charpy Impact, Notched	2.00 J/cm²	9.52 ft-lb/in²	ISO 179/1eA

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.20 %	<= 0.20 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China