

## Stir SpA SR 95 HT 105 CZ (PVC)

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Wire and Cable Grade

### Material Notes:

Application: Extrusion insulation CEI 20-11 type TI3 and YI8Information provided by STIR SpA

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Stir-SpA-SR-95-HT-105-CZ-PVC.php](http://www.lookpolymers.com/polymer_Stir-SpA-SR-95-HT-105-CZ-PVC.php)

| Physical Properties | Metric    | English                   | Comments |
|---------------------|-----------|---------------------------|----------|
| Density             | 1.37 g/cc | 0.0495 lb/in <sup>3</sup> | ISO 1183 |

| Mechanical Properties     | Metric   | English  | Comments  |
|---------------------------|----------|----------|-----------|
| Hardness, Shore A         | 95       | 95       | ISO 868   |
| Tensile Strength at Break | 17.2 MPa | 2490 psi | ISO R 527 |
| Elongation at Break       | 225 %    | 225 %    | ISO R 527 |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China