

## Styrolution Absolac® 380 ABS

Category : Polymer , Thermoplastic , ABS Polymer , Acrylonitrile Butadiene Styrene (ABS), Molded

### Material Notes:

High glossHigh flowInformation provided by Styrolution

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Styrolution-Absolac-380-ABS.php](http://www.lookpolymers.com/polymer_Styrolution-Absolac-380-ABS.php)

| Physical Properties | Metric                                                      | English                                                     | Comments |
|---------------------|-------------------------------------------------------------|-------------------------------------------------------------|----------|
| Melt Flow           | >= 35 g/10 min<br><br>@Load 10.0 kg,<br>Temperature 220 Â°C | >= 35 g/10 min<br><br>@Load 22.0 lb,<br>Temperature 428 Â°F | ISO 1133 |

| Mechanical Properties      | Metric         | English            | Comments |
|----------------------------|----------------|--------------------|----------|
| Izod Impact, Notched (ISO) | >= 13.0 kJ/mÂ² | >= 6.19 ft-lb/inÂ² |          |

| Thermal Properties    | Metric                        | English                      | Comments              |
|-----------------------|-------------------------------|------------------------------|-----------------------|
| Vicat Softening Point | 98.0 Â°C<br><br>@Load 5.10 kg | 208 Â°F<br><br>@Load 11.2 lb | 120Â°C/h; ASTM D 1525 |

| Optical Properties | Metric | English | Comments                         |
|--------------------|--------|---------|----------------------------------|
| Gloss              | 98 %   | 98 %    | Specular Gloss, 60Â°; ASTM D 523 |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China