

## Styron DL 396 Carboxylated SB

Category : Polymer , Thermoplastic , Styrene-Butadiene

### Material Notes:

Performance Features: Heat sealable, low odor, high water resistance, casein compatibilityApplications: Foil Lamination (FSK), Heat Sealable and Lamination (Metalized Paper)EuropeInformation provided by Styron

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Styron-DL-396-Carboxylated-SB.php](http://www.lookpolymers.com/polymer_Styron-DL-396-Carboxylated-SB.php)

| Physical Properties | Metric | English | Comments |
|---------------------|--------|---------|----------|
| Solids Content      | 50.5 % | 50.5 %  |          |
| pH                  | 5.7    | 5.7     |          |

| Thermal Properties        | Metric   | English  | Comments |
|---------------------------|----------|----------|----------|
| Glass Transition Temp, Tg | 10.0 Â°C | 50.0 Â°F |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China