

Suzhou Hipro Polymers Hiprolon® 200 NN Nylon 1010, dry

Category : Polymer , Renewable/Recycled Polymer , Thermoplastic , Nylon

Material Notes:

Hiprolon® 200 NN is a medium viscosity polyamide 10,10 with neat resin based on bio-renewable resource. It features low density, low water absorption, good cold impact resistance, good wear-resistance and flow ability. It is widely used as neat resin for compounding, general injection molding process, tubing or film extrusion, powder coating, et al. Information provided by Suzhou Hipro Polymers Co. Ltd

Order this product through the following link:

http://www.lookpolymers.com/polymer_Suzhou-Hipro-Polymers-Hiprolon-200-NN-Nylon-1010-dry.php

Physical Properties	Metric	English	Comments
Density	1.04 g/cc	0.0376 lb/in ³	ISO 1183
Water Absorption	0.70 %	0.70 %	ISO 62

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	60.0 MPa	8700 psi	ISO 527-1/-2
Elongation at Break	>= 50 %	>= 50 %	ISO 527-2/1A
Tensile Modulus	1.70 GPa	247 ksi	ISO 527-1/-2
Flexural Modulus	1.60 GPa	232 ksi	ISO 178

Thermal Properties	Metric	English	Comments
Melting Point	202 Â°C	396 Â°F	ISO 11357-1/-2
Deflection Temperature at 1.8 MPa (264 psi)	50.0 Â°C	122 Â°F	ISO 75-1/2

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China