

## Sylvin Technologies 8915-90 Natural PVC Extrusion Compound

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Extruded

### Material Notes:

Information provided by Sylvin Technologies Inc.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Sylvin-Technologies-8915-90-Natural-PVC-Extrusion-Compound.php](http://www.lookpolymers.com/polymer_Sylvin-Technologies-8915-90-Natural-PVC-Extrusion-Compound.php)

| Physical Properties | Metric    | English   | Comments |
|---------------------|-----------|-----------|----------|
| Specific Gravity    | 1.32 g/cc | 1.32 g/cc |          |

| Mechanical Properties      | Metric    | English  | Comments   |
|----------------------------|-----------|----------|------------|
| Hardness, Shore A          | 90        | 90       | 10 seconds |
| Tensile Strength, Ultimate | 19.13 MPa | 2775 psi |            |
| Elongation at Break        | 345 %     | 345 %    |            |
| Tear Strength Test         | 510       | 510      |            |

| Processing Properties | Metric        | English       | Comments |
|-----------------------|---------------|---------------|----------|
| Melt Temperature      | 171 - 182 Â°C | 340 - 360 Â°F |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China