

Taiwan Sheen Soon Sheenthane® AH-583 TPU for Hotmelt Adhesive

Category : Polymer , Thermoplastic , Elastomer, TPE , Polyurethane TPE , Polyurethane, TP

Material Notes:

Thermoplastic polyurethane elastomer for soft hotmelt adhesiveExcellent bonding strength for polyester, TPU, nylon, PVC, leather, fabrics, etc. Melt flow may be customized. Used for hot melt adhesive films, seam sealing tapes, heat transfer and fabric laminations, and automotive applications.Information provided by Taiwan Sheen Soon Co., LTD.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Taiwan-Sheen-Soon-Sheenthane-AH-583-TPU-for-Hotmelt-Adhesive.php

Physical Properties	Metric	English	Comments
Melt Flow	5.0 - 9.0 g/10 min	5.0 - 9.0 g/10 min	
	@Load 2.16 kg, Temperature 177 Â°C	@Load 4.76 lb, Temperature 351 Â°F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	78 - 82	78 - 82	

Thermal Properties	Metric	English	Comments
Softening Point	108 - 128 Â°C	226 - 262 Â°F	flow beginning

Descriptive Properties	Value	Comments
Tack-Free Time, min.	1 to 3	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China