

Teknor Apex APEX® 2570-H Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTMFeatures-Good FlexibilityUses-General Purpose, ProfilesAppearance-Natural Color, OpaqueForms-PelletsProcessing Method-ExtrusionInformation provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-2570-H-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.29 g/cc	1.29 g/cc	23°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	70	70	15 seconds; ASTM D2240
	76	76	ASTM D2240
Tensile Strength at Break	14.3 MPa	2080 psi	ASTM D412
Tensile Strength, Yield	5.07 MPa	735 psi	100%; ASTM D412
Elongation at Break	420 %	420 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-44.0 °C	-47.2 °F	ASTM D746

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China