

Teknor Apex APEXÂ® 3202-75 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTMUses-Caps, Closure, Connectors, Food

Service Applications, Safety Equipment, Valves/Valve Parts Appearance-ClearForms-PelletsProcessing Method-Injection

MoldingInformation provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-3202-75-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.22 g/cc	1.22 g/cc	23Â°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	75	75	15 seconds; ASTM D2240
Tensile Strength, Yield	16.5 MPa	2400 psi	ASTM D412
Elongation at Break	360 %	360 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-31.0 Â°C	-23.8 Â°F	ASTM D746

Processing Properties	Metric	English	Comments
Melt Temperature	177 Â°C	350 Â°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China