

Teknor Apex APEXÂ® 3302-85 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade

Material Notes:

Material Status-Commercial: ActiveAvailability-North AmericaTest Standards Available-ASTM Uses- Medical Applications, Tubing, Appearance-ClearForms-PelletsProcessing-ExtrusionInformation provided by Teknor Apex Company

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-3302-85-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.25 g/cc	1.25 g/cc	23Â°C; ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	85	85	15 seconds; ASTM D2240
Tensile Strength, Yield	11.0 MPa	1600 psi	100%; ASTM D412
	20.7 MPa	3000 psi	ASTM D412
Elongation at Break	340 %	340 %	ASTM D412

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-19.0 Â°C	-2.20 Â°F	ASTM D746

Processing Properties	Metric	English	Comments
Melt Temperature	182 Â°C	360 Â°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China