

Teknor Apex APEXÂ® 585 Polyvinyl Chloride, Flexible

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Flexible Grade , PVC, Wire and Cable Grade

Material Notes:

Notes: RoHS Compliant Features: General Purpose Uses: Tubing; Wire Jacketing Agency Ratings: UL 498; UL 62 Wire Types: SPT-1; SPT-2

Processing Method: ExtrusionForms: PelletsInformation Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-APEX-585-Polyvinyl-Chloride-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.21 g/cc	1.21 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	80	80	15 seconds; ASTM D2240
Tensile Strength at Break	17.2 MPa	2500 psi	ASTM D638
Elongation at Break	380 %	380 %	ASTM D638

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	50.0 Â°C	122 Â°F	Continuous Use; ASTM D794
Brittleness Temperature	-37.0 Â°C	-34.6 Â°F	ASTM D746

Descriptive Properties	Value	Comments
Appearance	Clear/Transparent	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China