

Teknor Apex Sinvicomp DBS 2006 Polyvinyl Chloride, Rigid

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Rigid Grade

Material Notes:

Notes: RoHS Compliant Availability: Asia Pacific Features: Ultra High Impact Resistance Uses: Piping Forms: Powder Processing Method: Extrusion Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-Sinvicomp-DBS-2006-Polyvinyl-Chloride-Rigid.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.40 g/cc	1.40 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	49.0 MPa	7110 psi	9.8 in/min; ASTM D638
Elongation at Break	150 %	150 %	20 in/min; ASTM D638
Izod Impact, Notched	4.43 J/cm	8.30 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	190 Â°C @Time >=1800 sec	374 Â°F @Time >=0.500 hour	Congo Red; BS 2782
Vicat Softening Point	80.0 Â°C	176 Â°F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China