

Teknor Apex Sinvicomp SRP 5602 Polyvinyl Chloride, Rigid

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Rigid Grade

Material Notes:

Availability: Asia Pacific Features: Good Processability Uses: Conduit; Piping; Profiles Forms: Pellets Processing Method:

Extrusion Information Provided by Teknor Apex

Order this product through the following link:

http://www.lookpolymers.com/polymer_Teknor-Apex-Sinvicomp-SRP-5602-Polyvinyl-Chloride-Rigid.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.43 g/cc	1.43 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	44.1 MPa	6400 psi	9.8 in/min; ASTM D638
Elongation at Break	150 %	150 %	9.8 in/min; ASTM D638
Izod Impact, Notched	0.801 J/cm	1.50 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	190 °C @Time >=Error in fixSigDigits: @digits must be between 1 a sec	374 °F @Time >=Error in fixSigDigits: @digits must be between 1 a hour	Congo Red; BS 2782
Vicat Softening Point	93.9 °C	201 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China