

## **ThyssenKrupp SECURE 400 Structural Steel**

Category: Metal, Ferrous Metal, Carbon Steel, Low Carbon Steel

## **Material Notes:**

This Material Specification applies to the alloyed, liquid-quenched and tempered high-strength special steel SECURE 400 for civil use, this is usually produced in thickness from 3 mm up to 50 mm. Application: The steels may be used for purposes of ballistic protection mainly for applications like armoured limousines and valuable transporters. Information Provided by Thyssen Krupp

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_ThyssenKrupp-SECURE-400-Structural-Steel.php

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	1150 MPa	167000 psi	
Tensile Strength, Yield	950 MPa	138000 psi	
Elongation at Break	11 %	11 %	
Charpy Impact	20.0 J	14.8 ft-lb	Transverse
	@Temperature -40.0 °C	@Temperature -40.0 °F	

Component Elements Properties	Metric	English	Comments
Aluminum, Al	<= 1.5 %	<= 1.5 %	
Carbon, C	<= 0.32 %	<= 0.32 %	
Chromium, Cr	<= 1.5 %	<= 1.5 %	
Manganese, Mn	<= 1.0 %	<= 1.0 %	
Molybdenum, Mo	<= 0.50 %	<= 0.50 %	
Nickel, Ni	<= 0.70 %	<= 0.70 %	
Phosphorous, P	<= 0.015 %	<= 0.015 %	
Silicon, Si	<= 0.40 %	<= 0.40 %	
Sulfur, S	<= 0.0050 %	<= 0.0050 %	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China