

Tra-Con Tra-Bond 724-17 Polyurethane Adhesive

Category : Polymer , Adhesive , Thermoset , Polyurethane, TS

Material Notes:

TRA-BOND 724-17 premixed and frozen, polyurethane adhesive is designed for good adhesion, providing strong resilient bonds to a wide variety of substrates, including aluminum, solder, nylon, mylar and steel. Adhesive strength is maintained even in cryogenic conditions. This resilient adhesive can be used for tacking wires and as a protective coating. Information provided by Tra-Con Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Tra-Con-Tra-Bond-724-17-Polyurethane-Adhesive.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	90	90	
Adhesive Bond Strength	6.89 MPa	1000 psi	Lap shear, alum to alum

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	125 °C	257 °F	Continuous
	125 °C	257 °F	
Minimum Service Temperature, Air	-55.0 °C	-67.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	180 min	3.00 hour	
	@Temperature 75.0 °C	@Temperature 167 °F	
	480 min	8.00 hour	
	@Temperature 60.0 °C	@Temperature 140 °F	
	2880 min	48.0 hour	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Descriptive Properties	Value	Comments
Color	Black	
Working Life minutes	30	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China