

Trelleborg AEM Eccofloat® TG-24/2000 Syntactic Foam

Category: Polymer

Material Notes:

TG Grade syntactic foams are lightweight and economical for building manned and remote operating vehicles. The foams are also used to manufacture mine neutralization systems because of their zero magnetic and sea-water comparable acoustic signatures. These composite foams provide ultra low densities by selecting only the highest specification hollow glass microspheres, called Eccospheres®, and combining them within a rigid, high strength resin system. The syntactic foam is typically cast into blocks and then is used to prepare large buoyancy modules that can be readily shaped to conform to hull contours and outfitted for installation in the forward and aft free-flood areas of submarines. All information provided by Trelleborg AEM.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Trelleborg-AEM-Eccofloat-TG-242000-Syntactic-Foam.php

Physical Properties	Metric	English	Comments
Density	0.384 g/cc	0.0139 lb/in³	

Mechanical Properties	Metric	English	Comments
Compressive Strength	20.7 MPa	3000 psi	Service Pressure

Descriptive Properties	Value	Comments	
Service Depth	2000 MSW	Depth Below Sea Level - Meters	
	6560 FSW	Depth Below Sea Level - Feet	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China