

Trelleborg AEM Syntac® 350 Syntactic Foam

Category : Polymer , Thermoset , Epoxy

Material Notes:

Syntac® 350 is made from high grade epoxy resin and hollow glass microspheres designed specifically for fabricating thermoforming plugs and other associated tooling. Available in block, sheet and rod form, Syntac® 350 is easily machined using standard shop tools and offers a lightweight, durable and cost effective alternative to wood, felt and aluminum. All information provided by Trelleborg Emerson & Cuming

Order this product through the following link:

http://www.lookpolymers.com/polymer_Trelleborg-AEM-Syntac-350-Syntactic-Foam.php

Physical Properties	Metric	English	Comments
Density	0.673 g/cc	0.0243 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	55	55	
	@Temperature 177 °C	@Temperature 350 °F	
Compressive Strength	44.8 MPa	6500 psi	
Compressive Modulus	2.34 GPa	339 ksi	

Thermal Properties	Metric	English	Comments
CTE, linear	30.6 µm/m-°C	17.0 µin/in-°F	
Specific Heat Capacity	2.09 J/g-°C	0.500 BTU/lb-°F	
Thermal Conductivity	0.121 W/m-K	0.840 BTU-in/hr-ft ² -°F	
Maximum Service Temperature, Air	177 °C	350 °F	

Descriptive Properties	Value	Comments
Color	White	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China