

Trelleborg Emerson & Cuming EP692 Sealer

Category : Polymer , Adhesive

Material Notes:

Sealer compatible with complete rangeAll information provided by Trelleborg Emerson & Cuming

Order this product through the following link:

http://www.lookpolymers.com/polymer_Trelleborg-Emerson-Cuming-EP692-Sealer.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.20 g/cc	1.20 g/cc	ASTM D792
Viscosity	3000 cP	3000 cP	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	87	87	ASTM D2240

Thermal Properties	Metric	English	Comments
CTE, linear	50.4 $\mu\text{m}/\text{m}\cdot\text{°C}$	28.0 $\mu\text{in}/\text{in}\cdot\text{°F}$	

Processing Properties	Metric	English	Comments
Pot Life	25 min	25 min	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Gel Time	180 - 300 min	180 - 300 min	Thin Film
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Descriptive Properties	Value	Comments
Color	Clear	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China