

Trelleborg Emerson & Cuming Stycast® 1265 Two-Component Easy Mix Ratio Encapsulant

Category : Polymer , Adhesive , Thermoset , Epoxy , Epoxy Encapsulant, Unreinforced

Material Notes:

Features and Typical Applications Primarily designed for ease of use in either meter mix or manual dispense operations. These products also offer a wide range of features including heat dissipation, thermal and mechanical shock resistance, and thermal conductivity. Emerson & Cuming 1265 Stycast® Two-Component Easy Mix Ratio Encapsulant Mix Ratio by weight = 100:100 Good Chemical Resistance Low Viscosity Cure Type: Heat Bonding Type: Epoxy

Order this product through the following link:

http://www.lookpolymers.com/polymer_Trelleborg-Emerson-Cuming-Stycast-1265-Two-Component-Easy-Mix-Ratio-Encapsulant.php

Physical Properties	Metric	English	Comments
Density	1.08 g/cc	0.0390 lb/in³	
Viscosity	600 cP @Temperature 25.0 °C	600 cP @Temperature 77.0 °F	Mixed

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	25	25	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	65.0 °C	149 °F	
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	

Electrical Properties	Metric	English	Comments
Dielectric Constant	3.0 @Frequency 1e+6 Hz	3.0 @Frequency 1e+6 Hz	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China