

Unipetrol BTX fraction

Category: Fluid, Solvent

Material Notes:

BTX fraction is manufactured by distillation of pyrolysis petrol. It is yellowish, highly combustible and easily inflammable liquid with strong aromatic odour. BTX fraction is mixture of aromatic hydrocarbons containing mainly benzene. Information provided by Unipetrol RPA

Order this product through the following link: http://www.lookpolymers.com/polymer_Unipetrol-BTX-fraction.php

| Physical Properties | Metric | English | Comments |
|---------------------|----------------------|------------------------------------|----------|
| Density | 0.850 - 0.870 g/cc | 0.0307 - 0.0314 lb/in ³ | |
| | @Temperature 15.0 °C | @Temperature 59.0 °F | |

| Component Elements Properties | Metric | English | Comments |
|-------------------------------|------------|------------|---------------|
| Sulfur, S | <= 0.010 % | <= 0.010 % | ASTM D3120-96 |

| Descriptive Properties | Value | Comments |
|----------------------------|-----------------------------------|----------|
| Brom Number Be2/100g, max | 25 | |
| Composition | 0.05 | |
| | 1 | |
| | 10 | |
| | 12 | |
| | 15 | |
| | 30 | |
| | 5 | |
| | 5 | |
| | 60 | |
| Diene Number J2/100 g, max | 3 | |
| Material | Benzene Content | |
| | C5 Hydrocarbons | |
| | C6 - C8 Non-aromatic Hydrocarbons | |
| | C9 + Hydrocarbons and higher | |
| | | |



| Descriptive Properties | Schylbenzene Content Value | Comments |
|------------------------|-------------------------------|----------|
| | Styrene Content | |
| | Toluene Content | |
| | Water Content | |
| | Xylenes Content | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China