

Unipetrol JET A-1 AFQRJOS Issue 18 Jet Kerosene

Category : Fluid , Solvent

Material Notes:

Jet Kerosene is a mixture of liquid hydrocarbons, with boiling point ranging between 135 and 280°C. It is obtained from crude oil by distillation and by other technological processes. It may contain additives to improve its usage characteristics. Jet kerosene is a flammable liquid class II of fire hazard, with flash point above 38°C. Information provided by Unipetrol RPA

Order this product through the following link:

http://www.lookpolymers.com/polymer_Unipetrol-JET-A-1-AFQRJOS-Issue-18-Jet-Kerosene.php

Physical Properties	Metric	English	Comments
Density	0.775 - 0.840 g/cc	0.0280 - 0.0303 lb/in ³	
Viscosity Measure	<= 8.0 cSt @Temperature -20.0 °C	<= 8.0 cSt @Temperature -4.00 °F	
Evaporation Loss	10 % @Temperature 205 °C	10 % @Temperature 401 °F	

Thermal Properties	Metric	English	Comments
Crystallization Temperature	<= -47.0 °C	<= -52.6 °F	
Flash Point	>= 38.0 °C	>= 100 °F	

Component Elements Properties	Metric	English	Comments
Sulfur, S	0.0030 %	0.0030 %	Mercaptan Sulfur
	0.30 %	0.30 %	

Descriptive Properties	Value	Comments
Appearance	Visually pure, light, without mechanical impurities and undissolved water at ambient temperature	
Aromatics Content (%), max	25	
Doctor Test	negative	
Resinous Content, mg/100cm ³ , max	7	
Sootless Flame Height mm	19	with 3% naphthalenes

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China