

Valley Adhesives EM-700 High Temperature Application Glue Stick

Category : Polymer , Adhesive , Thermoset

Material Notes:

Valley Adhesives EM-700 High Temperature Application Glue Stick Recommended for porous substrates; Bonds corrugated boxes, foam and carpeting.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Valley-Adhesives-EM-700-High-Temperature-Application-Glue-Stick.php

Physical Properties	Metric	English	Comments
Viscosity	4416 cP	4416 cP	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	68	68	
Tensile Strength, Ultimate	2.28 MPa	330 psi	
Elongation at Break	860 %	860 %	
Shear Strength	2.62 MPa	380 psi	
Peel Strength	4.05 kN/m	23.1 pli	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	60.0 °C	140 °F	Heat Resistance Value at 2 psi.
Softening Point	185 °C	365 °F	

Processing Properties	Metric	English	Comments
Cure Time	0.0833 min	0.00139 hour	Hot tack
Pot Life	0.33 min	0.33 min	Open Time

Descriptive Properties	Value	Comments
Color	Light Tan	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China