

Victrex® Vicote® F816 Black Polyetheretherketone (PEEK) Liquid Dispersion

Category: Polymer, Thermoplastic, Polyketone, Polyetheretherketone (PEEK)

Material Notes:

VICOTE® is the brand name for the Victrex range of coatings. VICOTE Coatings are available through Victrex or its preferred coater network. The VICOTE F815 and F816Blk grades have been specifically formulated to provide a coating that gives high wear and abrasion resistance combined with excellent release properties that are retained as the coating wears. These properties are retained at high temperatures where other release coatings would potentially fail. VICOTE dispersions have a low level of extractables..All information provided by Victrex.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Victrex-Vicote-F816-Black-Polyetheretherketone-PEEK-Liquid-Dispersion.php

Physical Properties	Metric	English	Comments
Storage Temperature	5.00 - 25.0 °C	41.0 - 77.0 °F	

Mechanical Properties	Metric	English	Comments
Impact	1.0	1.0	1m, 2kg, Indent 5mm; ISO 6272
Coefficient of Friction	0.15	0.15	μm @ 10 min., Using 250N Load; ASTM G 133

Processing Properties	Metric	English	Comments
Drying Temperature	120 °C	248 °F	overnight before use
	150 °C	302 °F	
	@Time 10800 sec	@Time 3.00 hour	

Descriptive Properties	Value	Comments
Color	Black	
Konig Hardness (seconds)	116	ISO 1522

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China