

Westlake Epolene® N-34 Nonemulsifiable - Low Molecular Weight Polyethylene Polymer

Category : Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

Product Description: Epolene N-34 is a polyethylene (PE) homopolymer that can easily be melt blended with natural or synthetic waxes to increase the tensile strength of wax blends, improve the gloss of paper coatings, aid in pigment dispersion and mold release, and improve scuff and rub off resistance in printing inks.
Key Attributes: Aids in pigment dispersion Easy to melt blend with natural or synthetic waxes Improves physical properties of paper coatings Increases scuff and rub off resistance in inks Low density polyethylene (PE)
Application/Uses: Building and Construction Hot Melt Adhesives Packaging Solventborne Adhesives Wax Modification Automotive

Order this product through the following link:

http://www.lookpolymers.com/polymer_Westlake-Epolene-N-34-Nonemulsifiable-Low-Molecular-Weight-Polyethylene-Polymer.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.910 - 0.950 g/cc	0.910 - 0.950 g/cc	
Viscosity	350 - 550 cP @Temperature 125 °C	350 - 550 cP @Temperature 257 °F	542-111
Brookfield Viscosity	450 cP @Temperature 125 °C	450 cP @Temperature 257 °F	
Molecular Weight	6200 g/mol	6200 g/mol	

Thermal Properties	Metric	English	Comments
Flash Point	>= 343 °C	>= 649 °F	ASTM E136
Ring & Ball Softening Point	104 °C	219 °F	ASTM E28

Optical Properties	Metric	English	Comments
Gardner Color Number	<= 2.0	<= 2.0	542-130

Descriptive Properties	Value	Comments
Penetration Hardness	5 dmm	ASTM D5, Needle under 100-g load for 5s @ 25 deg C, tenths of mm

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China